

MATERIAL SAFETY DATA SHEET

SNAP EDGE JR. PLASTIC EDGE RESTRAINT	
Material:	High density polyethylene 100%
Protection Required In Case of Contact:	*Eye protection, skin protection, respiratory protection, and ventilation - no special equipment required for ordinary conditions.
Waste Management:	Suitable for burning within a controlled burner for fuel value or supervised incineration - subject to applicable laws.
Toxicological Data:	Oral, dermal, and inhalation - non-toxic (estimated); Eye and skin irritation - expected to be non-irritating.
Regulatory Information:	DOT shipping class - not applicable; DOT hazard class - not applicable; U.S. O.S.H.A. - None
Reactivity Data:	Stability (thermal, light, etc.) - stable, avoid extreme heat, avoid strong oxidizers; Hazardous decomposition products - carbon monoxide, aldehydes, acetic acid; Leaching (contamination) of ground waters: negligible.
Fire and Explosion Data:	Flash point: 430°F (221°C); FLAMMABLE LIMITS - LEL: NA, UEL:NA; EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical and water fog. Firefighters must use self-contained breathing apparatus in enclosed areas.
Environmental Protection:	Contamination (leaching) of plasticizers into groundwater after long-term burial - expected to become negligible.
* Use glove and eye protection when handling, installing, bending, hammering, cutting, sawing and nailing SNAP EDGE JR. Good personal hygiene and safe work practices should always be used when working with SNAP EDGE JR.	

**IN CASE OF EMERGENCY CALL: CANADA 1-800-720-7627(SNAP)
U. S. A. 1-800-932-3343**